

AMENDMENTS TO CLAIMS

Please amend Claims 1-15 below by deleting items marked with a strikeout (i.e. ~~patent~~) or double brackets (i.e., ~~[[patent]]~~) and adding items marked with an underline (i.e. patent).

1. (Amended) An apparatus ~~[[and method]]~~ for rapid removal of fluids contained within reservoirs in automotive or similar transportation vehicles comprising:
- Al [[a)] a flexible hose having a proximal end opposite a distal end; ~~[[and]]~~ means of attachment of ~~[[the]]~~ said distal end of said hose to ~~[[the]]~~ a vehicle's ~~[[dipstick tube or similar access point to the]]~~ fluid reservoirs access point within the vehicle ;~~[[and]]~~
- [[b)] flexible hose with flow directional valve at said proximal end with coupling suitable for attachment to ~~[[the]]~~ a fill port of ~~[[the]]~~ a storage canister; and
- [[c)] said storage canister suitable to hold fluids of various viscosities' and corrosive characteristics ~~[[such as]]~~ selected from the group comprising oil, lubricants, cleaning agents, and coolants used within the vehicle.
2. (Amended) The storage container as claimed in claim 1 ~~[[having a volume usable for storage of more than one vehicle oil change]]~~ further comprising:
- a volume usable for storage of more than one vehicle oil change;
- [[a)] a fluid pump powered by an electric motor; and
- [[b)] a retractable power chord.

3. (Amended) The apparatus of claim 1 wherein said [[container]] storage canister further comprises:

[includes] a screen filter; and

a magnetic separator;

wherein aid filter and said separate [to] capture metallic debris and solid contaminants.

4. (Amended) The apparatus of claim 1 wherein said [[container includes]] storage canister comprises:

[inlet and outlet] at least one access [[ports]] port in fluid communication between an

interior of said container and an exterior of said container; and

[with] an integral seal and quick release hose attachment affixed to said port; and

a [with] spill proof check valve .

5. (Amended) The apparatus of claim 1 wherein said [[container]] storage canister is
provided with [wheel] wheel means to enable ease of positioning and movement of said
container.

6. (Amended) The apparatus of claim 5 wherein said [[positioning]] wheel means is
comprised [[in the preferred embodiment]] of a captured ball [[that facilitates]] capable of
facilitating steering through 360 degrees of directional change.

7. (Amended) The apparatus of claim ~~[[3]]~~ 4, where said ~~[[outlet and inlet]]~~ ports include an integral molded in place seal ~~[[similar to an o-ring]]~~ and ~~[[contain]]~~ a molded in place flow control valve ~~[[comprised in the preferred embodiment]]~~ of a reed / slit valve type.
8. (Amended) The apparatus of claim 1 wherein said ~~[[container]]~~ storage canister is fabricated ~~[[as a one piece molding made from a plastic such as polypropylene or as a weldment assembly of metallic components made]]~~ from corrosion resistant materials selected from the group comprising plastic, polypropylene, and metals such as 316L Stainless Steel ~~[[or]]~~ and Titanium.
9. (Amended) The apparatus of claim 1 wherein said ~~[[container is provided with the]]~~ storage canister further comprises means of determining fluid level ~~[[by employing transparent plastics, or incorporation of a fluid level gauge]]~~.
10. (Amended) The apparatus of claim 9 wherein said ~~[[fluid level gauge]]~~ means of determining fluid level is comprised ~~[[in the preferred embodiment]]~~ of a graduated flexible clear tube.
11. (Amended) The apparatus of claim ~~[[1]]~~ 6 wherein said ~~[[container]]~~ storage canister is provided with a handle that enables lifting the device, as well as transporting the device by tilting the device to an angle upon which the transport wheels are engaged to freely

rotate.

14

12. (Amended) The apparatus of claim [[1]] 2 wherein said [[container]] storage canister is provided with a self-retracting power chord.

13. (Amended) The apparatus of claim 12 wherein said power chord is comprised [[within the preferred embodiment]] of a flexible cable enclosing electrical conductors incorporating a constant force spring spool enabling ease of extraction and retraction.

AI cont
14. (Amended) The apparatus of claim [[1]] 2 wherein said fluid pump is [[comprised within the preferred embodiment as]] a positive displacement vane pump with reversible electric motor thus enabling pressure filling and pressure discharge of the fluids within the container.

15. (Amended) [[The]] A method for using the apparatus within claim 1, wherein the method for rapid removal of fluids from a vehicle [[is comprised]] comprises the steps:

- a) placement of the apparatus within a proximal distance of the vehicle[[and.]];
- b) connection of the fill flexible hose to the inlet port of the container; and[[.]]
- c) connection of the power chord to an active electrical outlet.

Please add the following new claims:

- 16 (New) An apparatus for removing the oils and lubricants from an automotive or similar transportation vehicles, said apparatus comprising:
- means of coupling to the vehicle's fluid reservoir;
 - a fluid storage canister;
 - an electrically driven positive displacement pump in fluid communication between said
 - Al* means of coupling to the vehicles fluid reservoir and said fluid storage container; and
 - automatic shut off means for controlling and stopping said pump when a desired amount
 - cont* of fluid is removed from said vehicle's fluid reservoir.
- 17 (New) The apparatus of claim 1, wherein said fluid storage container of a light-weight modular construction that enables ease of movement of the apparatus for storage and transport for disposable of the spent lubricants and oils.
-